

BLOWER WHEELS

Double Inlet, Belt Drive



Applications: Heating & Air Conditioning



- Galvanized, Universal Replacement Preslok® wheels
- Two hubs with center disc mechanically attached to each blade
- Strong Construction, CW or CCW rotation

DOUBLE INLET - BELT DRIVE

| Part Number | Lau Model | Bore Size | Set Screw | Key Way | Max. RPM | Y | W | D | X | U | Z | H |
|-------------|-----------|-----------|-----------|-------------|----------|--------|--------|--------|---------|-------|---------|----|
| 00866612 | A9-6A | 3/4 | 1 | 3/16 X 3/32 | 4000 | 9 1/2 | 6 | 9 1/2 | 7 11/16 | 1 1/4 | 2 15/16 | 43 |
| 00862112 | A9-7A | 3/4 | 1 | 3/16 X 3/32 | 3300 | 9 1/2 | 7 1/8 | 9 1/2 | 7 11/16 | 1 1/4 | 2 15/16 | 43 |
| 00851912 | A9-9A | 3/4 | 1 | 3/16 X 3/32 | 2400 | 9 1/2 | 9 1/2 | 9 1/2 | 7 11/16 | 1 1/4 | 2 15/16 | 43 |
| 00851916 | A9-9A | 1 | 1 | 1/4 X 1/8 | 2400 | 9 1/2 | 9 1/2 | 9 1/2 | 7 11/16 | 1 3/4 | 2 7/8 | 43 |
| 01223712 | A10-4A | 3/4 | 1 | 3/16 X 3/32 | 3900 | 10 5/8 | 4 1/2 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836412 | A10-6A | 3/4 | 1 | 3/16 X 3/32 | 3900 | 10 5/8 | 6 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836312 | A10-7A | 3/4 | 1 | 3/16 X 3/32 | 3100 | 10 5/8 | 7 1/8 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836112 | A10-8A | 3/4 | 1 | 3/16 X 3/32 | 3000 | 10 5/8 | 8 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836212 | A10-9A | 3/4 | 1 | 3/16 X 3/32 | 2300 | 10 5/8 | 9 1/2 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836012 | A10-10A | 3/4 | 1 | 3/16 X 3/32 | 2100 | 10 5/8 | 10 5/8 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836010 | A10-10A | 5/8 | 1 | 3/16 X 3/32 | 2100 | 10 5/8 | 10 5/8 | 10 5/8 | 8 7/8 | 1 1/4 | 3 9/32 | 48 |
| 00836016 | A10-10A | 1 | 1 | 1/4 X 1/8 | 2100 | 10 5/8 | 10 5/8 | 10 5/8 | 8 7/8 | 1 3/4 | 3 1/4 | 48 |
| 00897116 | A12-6A | 1 | 1 | 1/4 X 1/8 | 3800 | 12 5/8 | 6 | 12 5/8 | 10 5/16 | 1 3/4 | 3 1/2 | 43 |
| 02757515 | A12-9A | 3/4 | 1 | 3/16 X 3/32 | 2100 | 12 5/8 | 9 1/2 | 12 5/8 | 10 5/8 | 1 3/4 | 3 1/4 | 48 |
| 00850716 | A12-9A | 1 | 1 | 1/4 X 1/8 | 2500 | 12 5/8 | 9 1/2 | 12 5/8 | 10 5/16 | 1 3/4 | 3 1/2 | 43 |
| 00850758 | A12-9A | 1 3/16 | 1 | 1/4 X 1/8 | 2500 | 12 5/8 | 9 1/2 | 12 5/8 | 10 5/16 | 1 3/4 | 3 1/2 | 43 |
| 00850723 | A12-9A | 1 7/16 | 2 | 3/8 X 3/16 | 2500 | 12 5/8 | 9 1/2 | 12 5/8 | 10 5/16 | 2 1/2 | 3 7/8 | 43 |
| 00986716 | A12-11A | 1 | 1 | 1/4 X 1/8 | 2000 | 12 5/8 | 11 1/8 | 12 5/8 | 10 5/16 | 1 3/4 | 3 1/2 | 43 |
| 00840310 | A12-12A | 5/8 | 1 | 3/16 X 3/32 | 1800 | 12 5/8 | 12 5/8 | 12 5/8 | 10 5/16 | 1 1/4 | 3 3/8 | 43 |
| 00840301 | A12-12A | 3/4 | 1 | 3/16 X 3/32 | 1800 | 12 5/8 | 12 5/8 | 12 5/8 | 10 5/16 | 1 1/4 | 3 3/8 | 43 |
| 00840316 | A12-12A | 1 | 1 | 1/4 X 1/8 | 1800 | 12 5/8 | 12 5/8 | 12 5/8 | 10 5/16 | 1 3/4 | 3 1/2 | 43 |
| 00840393 | A12-12A | 1 3/16 | 1 | 1/4 X 1/8 | 1800 | 12 5/8 | 12 5/8 | 12 5/8 | 10 5/16 | 2 1/2 | 3 7/8 | 43 |
| 00840379 | A12-12A | 1 7/16 | 2 | 3/8 X 3/16 | 1800 | 12 5/8 | 12 5/8 | 12 5/8 | 10 5/16 | 2 1/2 | 3 7/8 | 43 |
| 00874716 | A12-15A | 1 | 1 | 1/4 X 1/8 | 1100 | 12 5/8 | 15 | 12 5/8 | 10 5/16 | 1 3/4 | 3 1/2 | 43 |
| 00954816 | A15-9A | 1 | 1 | 1/4 X 1/8 | 2500 | 15 | 9 1/2 | 15 | 12 5/8 | 1 3/4 | 4 1/8 | 51 |
| 00954870 | A15-9A | 1 3/16 | 2 | 1/4 X 1/8 | 2500 | 15 | 9 1/2 | 15 | 12 5/8 | 2 1/2 | 4 1/2 | 51 |

Maximum Operating Temperature, 200°F.

Continued on next page.

Specifications are subject to change without notice or obligation

DOUBLE INLET - BELT DRIVE


| Part Number | Lau Model | Bore Size | Set Screw | Key Way | Max. RPM | Y | W | D | X | U | Z | H |
|--------------|-----------|--------------------------------|-----------|------------|----------|--------|--------|--------|----------|-------|--------|----|
| 00954823 | A15-9A | 1 ⁷ / ₁₆ | 2 | 3/8 x 3/16 | 2500 | 15 | 9 1/2 | 15 | 12 5/8 | 2 1/2 | 4 1/2 | 51 |
| 00841816 | A15-11A | 1 | 1 | 1/4 x 12 | 2100 | 15 | 11 1/8 | 15 | 12 5/8 | 1 3/4 | 4 1/8 | 51 |
| 00841877 | A15-11A | 1 3/16 | 1 | 1/4 x 12 | 2100 | 15 | 11 1/8 | 15 | 12 5/8 | 1 3/4 | 4 1/8 | 51 |
| 00841880 | A15-11A | 1 7/16 | 2 | 3/8 x 3/16 | 2100 | 15 | 11 1/8 | 15 | 12 5/8 | 2 1/2 | 4 1/2 | 51 |
| 00874616 | A15-12A | 1 | 1 | 1/4 x 12 | 1900 | 15 | 12 5/8 | 15 | 12 5/8 | 1 3/4 | 4 1/8 | 51 |
| 00827616 | A15-15A | 1 | 1 | 1/4 x 12 | 1550 | 15 | 15 | 15 | 12 5/8 | 1 3/4 | 4 1/8 | 51 |
| 01767137 | A15-15A | 1 3/16 | 1 | 1/4 x 12 | 1550 | 15 | 15 | 15 | 12 5/8 | 1 3/4 | 4 1/8 | 51 |
| 00827672 | A15-15A | 1 7/16 | 2 | 3/8 x 3/16 | 1550 | 15 | 15 | 15 | 12 5/8 | 2 1/2 | 4 1/2 | 51 |
| 00865916 | A18-13A | 1 | 1 | 1/4 x 12 | 1550 | 18 5/8 | 13 1/2 | 18 1/8 | 14 11/16 | 1 3/4 | 5 | 48 |
| 00865960 | A18-13A | 1 7/16 | 1 | 1/4 x 12 | 1550 | 18 5/8 | 13 1/2 | 18 1/8 | 14 11/16 | 1 3/4 | 5 | 48 |
| 00865816 | A18-18A | 1 | 1 | 1/4 x 12 | 1200 | 18 5/8 | 18 | 18 1/8 | 14 11/16 | 1 3/4 | 5 | 48 |
| 00865874 | A18-18A | 1 3/16 | 1 | 1/4 x 12 | 1200 | 18 5/8 | 18 | 18 1/8 | 14 11/16 | 1 3/4 | 5 | 48 |
| 00865887 | A18-18A | 1 7/16 | 2 | 3/8 x 3/16 | 1200 | 18 5/8 | 18 | 18 1/8 | 14 11/16 | 2 1/2 | 5 3/8 | 48 |
| (A)01954002 | A20-18A | 1 3/16 | 1 | 1/4 x 12 | 1100 | 20 1/2 | 18 | 20 | 16 9/16 | 2 1/2 | 5 3/32 | 53 |
| (A)01954041 | A20-18A | 1 7/16 | 2 | 3/8 x 3/16 | 1100 | 20 1/2 | 18 | 20 | 16 9/16 | 2 1/2 | 5 3/32 | 53 |
| (A)01954029 | A20-18A | 1 11/16 | 1 | 3/8 x 3/16 | 1100 | 20 1/2 | 18 | 20 | 16 9/16 | 2 3/4 | 5 3/32 | 53 |
| (A)01954020 | A20-18A | 2 15/16 | 1 | 1/2 x 1/4 | 1100 | 20 1/2 | 18 | 20 | 16 9/16 | 4 1/4 | 5 3/32 | 53 |
| (A)02043907* | A20-18A | 3* | — | N/A | 1100 | 20 1/2 | 18 | 20 | 16 9/16 | 5 3/4 | 5 3/32 | 53 |
| (A)02043920* | A20-18A | 4* | — | N/A | 1100 | 20 1/2 | 18 | 20 | 16 9/16 | 7 1/8 | 5 3/32 | 53 |

(A) These wheels are a special order with 2 - 4 weeks lead time required and **CANNOT ship by UPS.**

* Clamplok Hubs with a diameter of 1 3/16" and larger include tapped holes at 90° to keyway for accepting 2nd SS (supplied by installer).

REDUCING BUSHINGS - FOR ABOVE WHEELS ONLY

(Use to reduce wheel bore sizes)



• **A 1" bore wheel can be reduced to a 3/4" bore by using bushings with a 1" O.D. and a 1/8" I.D.**

| Part Number | Model / Description |
|-------------|--|
| 02750203 | 1" O.D. x 3/4" I.D. x 1 1/8" long 1 1/8" |

Order the quantity of bushings to match number of hubs in the wheel.

Use reducer bushings (one for each hub) if a smaller bore size is required.

NUMBER OF BLADES

